








Accessories

Heat Recovery Systems

Part Number	Item	
4016011	56 in. Magnesium Anode A one-piece solid replacement anode, the same as is installed in new Opti-Stor tanks. 3/4 in. NPT.	
4016054	58 in. Linked Magnesium Anode The linked anode makes replacement easier in low clearance installations. The anode is made from a chain of 12 in. links to facilitate easy removal and installation. 3/4 in. NPT.	
4021110	Drain Valve Kit When installed near the water inlet of an Opti-Stor, allows for easy draining of the tank. Includes hose bib, tee, reducing elbow, union and di-electric connector.	
4018285	Aquastat The aquastat provides temperature sensing and Set point in order to control accessories like a water bleed valve or a three way heat reclaim valve. The bulb is mounted on a 5.5 ft. capillary for use with 4018286 immersion well. Range: 40 to 180°F. SPST action, break on rise. Electrical: 120V, 8A / 240V, 5.1A.	
4018286	Immersion Well The immersion well allows the temperature sensor of the 4018285 aquastat to be immersed into the water tank of any Opti-Stor for more accurate temperature sensing. The well can be installed in place of the mid-port stub, replace an anode in the top of the tank, or be incorporated into the hot water supply piping.	
4021111	Aquastat / Strap-on The strap-on aquastat provides an easy, unobtrusive way to sense and control water temperatures. Range: 100 to 240°F. SPDT action, make or break on rise. Electrical: 120V, 7.4A / 240V, 3.7A.	
4023228	Stand The stand is designed to raise an Opti-Stor Heat Reclaim Water Heater 6 in. off the floor. This will satisfy NSF requirements. Designed specifically for Opti-Stor 120 gallon tanks (80 gallon Opti-Stor uses 4033335).	

Accessories | Heat Recovery Systems

Part Number	Item	
4034929	Dielectric Extender 3/4 in. NPT x 2 in. Installation accessory for Opti-Stor plumbing.	
1407752	Galvanized Reducing Tee 1-1/4 in. x 3/4 in. x 1-1/4 in. Installation accessory for Opti-Stor plumbing.	
1403405	Galvanized Nipple 1-1/4 in. x 2-3/4 in. Installation accessory for Opti-Stor plumbing.	
1400803	Galvanized Cap 3/4 in. Installation accessory for Opti-Stor plumbing.	
4020716	Temperature/Pressure Relief Valve 210/150. Service part for multiple Opti-Stor models.	
4022853	Thermostat 120-180°F. Service part for select Opti-Stor TS III models.	
4024196	Thermostat, SPDT SPDT, 110-170°F. Service part for select Opti-Stor TS III models.	
4017665	Heating Element 6000W, 240V. Service part for 240V Opti-Stor TS III models.	
4021954	Heating Element 6000W, 480V. Service part for 480V Opti-Stor TS III models.	
4041955	Thermowell Kit Installation accessory for Opti-Stor tank installations. SS Thermowell kit includes a junction box.	
4018232	Short Insulator For Thermostat.	